7.2.1 1FK7 Compact

Table7-1 1FK7011 CT

Technical data	Code	Units	–5AK71	
Configuration data				
Rated speed	n_N	RPM	6000	
No. of poles	2p		8	
Rated torque (100 K)	$M_{N\ (100\ K)}$	Nm	0.08	
Rated current (100 K)	I_N	A	0.85	
Static torque (60 K)	$M_{0\ (60\ K)}$	Nm	0.15	
Static torque (100 K)	$M_{0\ (100\ K)}$	Nm	0.18 1.2	
Stall current (60 K)	$I_{0\ (60\ K)}$	A	1.5	
Stall current (100 K)	$I_{0\ (100\ K)}$	A	0.083	
Moment of inertia (with brake)	J_{MotBr}	10^{-4} kgm^2	0.064	
Moment of inertia (without brake)	J_{Mot}	10^{-4} kgm^2		
Optimum operating point	n_{opt}	RPM	5000	
Optimum speed	P_{opt}	kW	0.06	
Optimum power	$n_{max\ mech}$	RPM	8000	
Limiting data	$n_{max\ Inv}$	RPM	8000	
Max. permissible speed (mech.)	M_{max}	Nm	0.5	
Max. permissible speed (converter)	I_{max}	A	4.2	
Max. torque	k_T	Nm/A	0.12	
Max. current	k_E	V/1000 RPM	8	
Physical constants	R_{Str}	Ohm	3	
Torque constant	L_D	mH	4.2	
Voltage constant	T_{el}	ms	1.4	
Winding resistance at 20°C	T_{mech}	ms	4	
Cyclic inductance	T_{th}	min	14 1400	
Electrical time constant	c_t	Nm/rad	1.0	
Mechanical time constant	m_{MotBr}	kg	0.9	
Thermal time constant	m_{Mot}	kg		
Shaft torsional stiffness			3	
Weight with brake			6	
Weight without brake		A	0.5	
Recommended motor module 6SL312_-_TE13-0AA_		A		
		Nm		
Rated current converter	$I_{N\ Inv}$			
Max. current converter	$I_{max\ Inv}$			
Max. torque at $I_{max\ Inv}$	$M_{max\ Inv}$			

e-Servo

For motor		Dimensions in mm (in)											Resolver					
													without brake			with		
Shaft height	Type	DIN IEC	a_1 P	b_1 N	c_1 LA	e_1 M	f AB	f_1 T	g_2 –	h H	i_2 –	s_2 S	k LB	o_1 –	o_2 –	brake ko_1 LB–	o_2 –
1FK7 Compact, type IM B5, natural cooling, with connector, with/without brake																		
20	1FK7011-5	–		30 (1.18)	7 (0.28)	46 (1.81)	40 (1.57)	2.5 (0.10)	65.5 (2.58)	20 (0.79)	18 (0.71)	4.5 (0.18)	140 (5.51)	89 (3.50)	118 (4.65)	140 (5.51)	89 (3.50)	118 (4.65)
	1FK7015-5	–		30 (1.18)	7 (0.28)	46 (1.81)	40 (1.57)	2.5 (0.10)	65.5 (2.58)	20 (0.79)	18 (0.71)	4.5 (0.18)	165 (6.50)	114 (4.49)	143 (5.63)	165 (6.50)	114 (4.49)	143 (5.63)
28	1FK7022-5	–		40 (1.57)	10 (0.39)	63 (2.48)	55 (2.17)	2.5 (0.10)	75 (2.95)	27.5 (1.08)	20 (0.79)	5.4 (0.21)	153 (6.02)	95 (3.74)	128 (5.04)	175 (6.89)	95 (3.74)	150 (5.91)
36	1FK7032-5		92 (3.62)	60 (2.36)	8 (0.31)	75 (2.95)	72 (2.83)	3 (0.12)	81 (3.19)	36 (1.42)	30 (1.18)	6.5 (0.26)	150 (5.91)	90 (3.54)	125 (4.92)	175 (6.89)	90 (3.54)	149 (5.87)
	1FK7034-5		92 (3.62)	60 (2.36)	8 (0.31)	75 (2.95)	72 (2.83)	3 (0.12)	81 (3.19)	36 (1.42)	30 (1.18)	6.5 (0.26)	175 (6.89)	115 (4.53)	150 (5.91)	200 (7.87)	115 (4.53)	174 (6.85)
48	1FK7040-5		120 (4.72)	80 (3.15)	10 (0.39)	100 (3.94)	96 (3.78)	3 (0.12)	90 (3.54)	48 (1.89)	40 (1.57)	7 (0.28)	134 (5.28)	73 (2.87)	106 (4.17)	163 (6.42)	73 (2.87)	135 (5.31)
	1FK7042-5		120 (4.72)	80 (3.15)	10 (0.39)	100 (3.94)	96 (3.78)	3 (0.12)	90 (3.54)	48 (1.89)	40 (1.57)	7 (0.28)	162 (6.38)	101 (3.98)	134 (5.28)	191 (7.52)	101 (3.98)	163 (6.42)
63	1FK7060-5		155 (6.10)	110 (4.33)	10 (0.39)	130 (5.12)	126 (4.96)	3.5 (0.14)	105 (4.13)	63 (2.48)	50 (1.97)	9 (0.35)	157 (6.18)	94 (3.70)	126 (4.96)	200 (7.87)	94 (3.70)	169 (6.65)
	1FK7063-5		155 (6.10)	110 (4.33)	10 (0.39)	130 (5.12)	126 (4.96)	3.5 (0.14)	105 (4.13)	63 (2.48)	50 (1.97)	9 (0.35)	202 (7.95)	139 (5.47)	171 (6.73)	245 (9.65)	139 (5.47)	214 (8.43)

		Basic absolute encoder (EnDat) (shaft height 48 and larger), Incremental encoder sin/cos1 V_{pp}						Absolute encoder (EnDat)										
		without brake			with brake			without brake			with							
Shaft height	Type	k LB	o_1 –	o_2 –	k LB	o_1 –	o_2 –	k LB	o_1 –	o_2 –	brake ko_1 LB–	o_2 –	d D	d_6 –	l E	t GA	u F
20	1FK7011-5	155 (6.10)	89 (3.50)	118 (4.64)	155 (6.10)	89 (3.50)	118 (4.64)	155 (6.10)	98 (3.50)	118 (4.64)	155 (6.10)	89 (3.50)	118 (4.64)	8 (0.31)	M3	18 (0.71)	8.8 (0.35)	2 (0.08)
	1FK7015-5	180 (7.08)	114 (4.48)	143 (5.63)	180 (7.08)	114 (4.48)	143 (5.63)	180 (7.08)	114 (4.48)	143 (5.63)	180 (7.08)	114 (4.48)	143 (5.63)	8 (0.31)	M3	18 (0.71)	8.8 (0.35)	2 (0.08)
28	1FK7022-5	178 (7.01)	95 (3.74)	128 (5.04)	200 (7.87)	95 (3.74)	150 (5.91)	178 (7.01)	95 (3.74)	128 (5.04)	200 (7.87)	95 (3.74)	150 (5.91)	9 (0.35)	M3	20 (0.79)	10.2 (0.40)	3 (0.12)
36	1FK7032-5	175 (6.89)	90 (3.54)	125 (4.92)	200 (7.87)	90 (3.54)	149 (5.87)	175 (6.89)	90 (3.54)	125 (4.92)	200 (7.87)	90 (3.54)	149 (5.87)	14 (0.55)	M5	30 (1.18)	16 (0.63)	5 (0.20)
	1FK7034-5	200 (7.87)	115 (4.53)	150 (5.91)	225 (8.86)	115 (4.53)	174 (6.85)	200 (7.87)	115 (4.53)	150 (5.91)	225 (8.86)	115 (4.53)	174 (6.85)	14 (0.55)	M5	30 (1.18)	16 (0.63)	5 (0.20)
48	1FK7040-5	155 (6.10)	73 (2.87)	106 (4.17)	184 (7.24)	73 (2.87)	135 (5.31)	163 (6.42)	73 (2.87)	106 (4.17)	192 (7.56)	73 (2.87)	135 (5.31)	19 (0.75)	M6	40 (1.57)	21.5 (0.85)	6 (0.24)
	1FK7042-5	182 (7.17)	101 (3.98)	134 (5.28)	211 (8.31)	101 (3.98)	163 (6.42)	191 (7.52)	101 (3.98)	134 (5.28)	220 (8.66)	101 (3.98)	163 (6.42)	19 (0.75)	M6	40 (1.57)	21.5 (0.85)	6 (0.24)
63	1FK7060-5	180 (7.09)	94 (3.70)	126 (4.96)	223 (8.78)	94 (3.70)	169 (6.65)	188 (7.40)	94 (3.70)	126 (4.96)	231 (9.09)	94 (3.70)	169 (6.65)	24 (0.94)	M8	50 (1.97)	27 (1.06)	8 (0.31)
	1FK7063-5	225 (8.86)	139 (5.47)	171 (6.73)	268 (10.55)	139 (5.47)	214 (8.43)	233 (9.17)	139 (5.47)	171 (6.73)	276 (10.87)	139 (5.47)	214 (8.43)	24 (0.94)	M8	50 (1.97)	27 (1.06)	8 (0.31)

1FK701 . –5
1FK702 . –5
1FK703 . –5
1FK704 . –5
1FK706 . –5

Shaft design with fitted key



e-Servo